



Transport Dollies F30 / L30

Features:

- L dolly- swivel plate to facilitate steering
- F dolly- width adjustable points of contact
- Durable, non-marking rollers
- Thick, grooved rubber pads to prevent load slippage



| Technical data | F30 | L30 |
|---|-----------------------------------|--------------------------------|
| Item number | 3-11992 | 3-11993 |
| Loading height / number of wheels (140 x 85mm) | 7.1" / 12 180 mm / 12 | 7.1" / 12 180 mm / 12 |
| Contact surface per cartridge | 11.8 x 11.2" / 300 x 285 mm | — |
| Connecting bar | 25.6 - 72" / 650 x 1830 mm | — |
| Swivel plate ø 250 mm, steering angle | — | ±90° |
| Steering rod | 55.9" / 1420 mm | 63.8" / 1620 mm |
| Overall dimensions (L x W) | 11.8 x 58.7" / 300 x 1490 mm | 32.3 x 37.4" / 820 x 950 mm |
| Weight | 282 lbs. / 128 kg | 472 lbs. / 214 kg |
| Load capacity per unit | 66,000 lbs. / 300 kN (30 t) | 66,000 lbs. / 300 kN (30 t) |
| Combined load capacity | 132,000 lbs. / 600 kN (60 t) | |

